

K4EFBP05VVL

ELECTRIC LOW-BUILT GRIDDLE PLATE SMOOTH PLATE + OPEN CABINET -
PERFORMANCE LINE



PRODUCT DESCRIPTION

Stainless steel frame. Athermic thermoset plastic knobs with useful screen printed edges.

Heating obtained through **radiant heating elements** placed under the cooking plate. Thermostat to adjust the temperature of the plate between 120°C and 320°C. Safety thermostat with manual reset.

Single large-size low-built cooking plate made of special stainless steel and processed with a smooth finish that allows excellent heat transmission and **mirror polished finishing** to ensure non-stick food and quick cleaning in compliance with current regulations.

Smooth cooking plate.

Sloping worktop facing the fat drain hole. **Large hole on the cooking surface** for draining fats into **a provided container with a capacity of 2.9 liters** below the cooking surface itself.

Moulded AISI 304 stainless steel worktop with rounded edges for easy cleaning. Stainless steel front, side and back panels.

A Teflon plug, suitable to plug the drain in case of any cooking with a film of oil, available **on demand**.

Laser-cut work top finishing for "head-to-head" matching and binding fastening.

Height-adjustable stainless steel legs.

Accessories available **on demand**.



TECHNICAL SPECIFICATIONS

Width: 400 mm

Depth: 900 mm

Height: 850 mm

Weight: 58 kg

Volume: 0.56 m³

Electrical power: 7.00 kW

