

# K4EGDP05TT

ELECTRIC DIRECT GRIDDLE 1/2 MODULE TOP



## PRODUCT DESCRIPTION

Stainless steel frame. Athermic thermoset plastic knobs with useful screen printed edges.

Heating obtained through **heating elements with AISI 304 sheath**, which work in air and are suitable for the temperatures to which they are exposed (400°C). The heat load of the heating elements allows **heat exchange only towards the food to improve** cooking and energy savings. Safety thermostat with automatic reset to protect the heating elements. Energy regulator adjusting the frequency of ON-OFF operation of the heating elements. The maximum continuous operation position is useful in the cleaning process, as it induces pyrolysis of the fats on the heating elements.

**AISI 304 cold-pressed water tank with drain hole.** The water improves the quality of the food cooked and carries the cooking fats to the drain.

**Tap for filling and refilling water** placed on the frontal panel. **Tank drain** placed on the frontal panel and operated by a lever.

2 mm thick moulded AISI 304 stainless steel worktop with rounded edges for easy cleaning. Stainless steel front, side and back panels.

Laser-cut work top finishing for "head-to-head" matching and binding fastening.

Accessories available **on demand**.



## TECHNICAL SPECIFICATIONS

**Width:** 400 mm  
**Depth:** 900 mm  
**Height:** 250 mm  
**Weight:** 48 kg  
**Volume:** 0.26 m<sup>3</sup>  
**Electrical power:** 5.40 kW

