

K4MCU10FFS

GAS RANGE 4 BURNERS + ELECTRIC OVEN 2/1 GN - SOLUTION LINE



PRODUCT DESCRIPTION

Stainless steel frame. Athermic thermoset plastic knobs with useful screen printed edges. Double-skinned moulded oven door and heavy-duty handle.

Heating by means of cast-iron, sealed, stabilised flame and superimposed double crown burners with different power ratings (max. 8.5 kW and 10.7 kW).

Each burner provided with a safety gas cock, which enables the output to be regulated **from maximum to minimum**. Safety ensured by a thermocouple kept active by the burner flame.

Surface grids made of alkali-, acid- and fire-resistant RAAF matt enamelled cast iron.

Surface grids placed on moulded surfaces with rounded edges and water-tight burners for easy cleaning.

Worktop drain through overflow available on request to speed up cleaning operations.

Electric static oven 2/1 GN. Stainless steel AISI 430 oven cooking chamber and thick stainless steel oven floor. Stainless steel removable oven grill.

Insulation of the cooking chamber and of the oven door ensured by a layer of high temperature resistant ceramic fibre.

Heating obtained through heating elements placed under the bottom and on the top of the cooking chamber. Equipped with a thermostat that adjusts the temperature between 90°C and 300°C.

Moulded AISI 304 stainless steel worktop with rounded edges for easy cleaning. Stainless steel front, side and back panels. Laser-cut work top finishing for "head-to-head" matching and binding fastening.

Tested with natural gas or LPG, according to the user's needs.

Height-adjustable stainless steel legs.

Accessories available on demand.









TECHNICAL SPECIFICATIONS

Width: 800 mm Depth: 900 mm Height: 850 mm Weight: 115 kg Volume: 0.99 m³

Electrical power: 5.40 kW Gas power: 38.40 kW





