

## K7GFB05TTL

GAS LOW-BUILT GRIDDLE PLATE SMOOTH STEEL TOP - PERFORMANCE LINE



## PRODUCT DESCRIPTION

Stainless steel frame. Athermic thermoset plastic knobs with useful screen printed edges.

**Quick temperature rise** and heat retention achieved by **2-branch burners with optimized combustion**, suitable for working at high temperatures, with thermostatically controlled 8-position thermocouple safety valve and pilot flame. Temperature regulation **between 150°C** and **315°C**. Safety ensured by a thermocouple kept active by the pilot burner flame.

Single large-size low-built cooking plate made of special stainless steel and processed with a smooth finish that allows excellent heat transmission and mirror polished finishing to ensure non-stick food and quick cleaning in compliance with current regulations. Smooth cooking plate.

Sloping worktop facing the fat drain hole. Large hole on the cooking surface for draining fats into a provided container with a capacity of 1.3 liters below the cooking surface itself.

Moulded AISI 304 stainless steel worktop with rounded edges for easy cleaning. Stainless steel front, side and back panels.

A Teflon plug, suitable to plug the drain in case of any cooking with a film of oil, available on demand.

Laser-cut work top finishing for "head-to-head" matching and binding fastening.

Tested with natural gas or LPG, according to the user's needs.

Accessories available on demand.









## **TECHNICAL SPECIFICATIONS**

Width: 400 mm Depth: 700 mm Height: 250 mm Weight: 32 kg Volume: 0.21 m³ Gas power: 7.00 kW





