

# AF521

FRONT-LOADING DISHWASHER - TOTAL POWER 3,5 KW



## PRODUCT DESCRIPTION

### BEST WASH

Stainless steel structure and tank 18/10 AISI 304. Wide double-skinned balanced door.

Stainless steel upper and lower coplanar wash and rinse arms.

Stainless steel heating elements, resistant to corrosion and limescale.

Temperature thermometer. Possibility to change the cycle parameters.

The programmable **THERMOLOCK** system ensures that the rinsing cycle starts only at the temperature of 85°C: the ideal temperature for strongly reducing the bacterial load.

**Standard equipped** with built-in rinse aid dispenser for the best drying results. **Standard equipped** with built-in connection for detergent dispenser.

**Standard equipped** with built-in connection for drain pump. **Standard equipped** with built-in connection for WiFi module.

Wide range of options available **on demand**. **Standard equipped** with a basket for plates and a basket for cups.

Performance Line stands as the more matching the needs of those chefs looking for the best washing performance. Brilliant washing results thanks to its cycles: it is possible to optimize the washing performances according to the type of crockery.

Highly resistant and anti-scratch capacitive display, designed to bear with any modern kitchen stress.



## TECHNICAL SPECIFICATIONS

**Width:** 600 mm

**Depth:** 600 mm

**Height:** 820 mm

**Volume:** 0.30 m<sup>3</sup>

**Rack dimensions:** 500x500 mm

**Useful height:** 330

**Electrical power:** 3.50 kW

**Electric power:** 230 V / 1 - 230 V / 3 - 400 V / 3+N/ 50-60 Hz

**Dishes/Hour:** 1080-108

