



AF881

FRONT-LOADING DISHWASHER - TOTAL POWER 6,8 KW



PRODUCT DESCRIPTION

WASH EURONORMS TRAYS!

Stainless steel structure 18/10 AISI 304. Double-skinned balanced and moulded door for easily taking out the basket. Wash tank with rounded edges and inclination, thus ensuring the complete drainage of dirty water.

Stainless steel upper and lower wash and rinse arms.

Stainless steel surface filter in the tank for collecting solid waste.

Temperature thermometer. Possibility to change the cycle parameters.

The programmable THERMOLOCK system ensures that the rinsing cycle starts only at the temperature of 85°C: the ideal temperature for strongly reducing the bacterial load.

Standard equipped with built-in rinse aid dispenser for the best drying results. Standard equipped with built-in connection for detergent dispenser.

Standard equipped with the connection for the WiFi module.

Wide range of options available on demand. Standard equipped with a basket for plates and a basket for cups.

Double water filtration system with stainless steel filters helps you in keeping water cleaner for longer. 20% less water is needed in the washing tank as compared to the model AF56 for energy and detergent savings.

Double-skinned, insulated washing tank increases your comfort thanks to lower noise and remarkable energy savings.

Extremely versatile: thanks to its wide door opening of 40 cm it can wash even Eurornorms trays.

Maximum ergonomics! The increased working height at 1.2 mt means that loading and unloading basket is easier.

Highly resistant and anti-scratch capacitive display, designed to bear with any modern kitchen stress.









TECHNICAL SPECIFICATIONS

Width: 600 mm Depth: 600 mm Height: 1275 mm

Rack dimensions: 500x500 mm

Useful height: 405 Electrical power: 6.80 kW

Electric power: 230 V/ 3 - 400 V / 3+N/ 50-60 Hz

Dishes/Hour: 1080-108





