

ATR3800ES

RACK CONVEYOR DISHWASHER LEFT-HAND SIDE ENTRY 3800 PLATES PER HOUR



PRODUCT DESCRIPTION

ATR3800 ES: Rack conveyor dishwasher with electric feeding and left-hand side rack entry

Stainless steel structure 18/10 AISI 304. Sturdy counter-balanced door. Wash tank with rounded edges and inclination, thus ensuring the complete drainage of dirty water.

Stainless steel upper and lower wash and rinse arms that can be easily taken out for cleaning.

One pre-washing area, one washing area and a double rinsing area.

Three-speed rack movement with a washing capacity of 110 racks/hour (speed 1) or 160 racks/hour (speed 2) or 210 racks/hour (speed 3).

High capacity double-boiler system.

Double stainless steel surface filters in the tank with an easily removable basket for collecting solid waste.

Compact geared motor with integrated clutch.

Ergonomic control panel in order to make the temperatures and the different working steps easily recognisable.

Possibility to program the water temperature in each wash tank and to set the rinsing temperature.

Standard equipped with non-return valve avoiding dirty water flowing back into the main water system (DVGW approved).

Standard equipped with stainless steel connection for detergent dispenser in each wash tank. Standard equipped with built-in connection for detergent dispenser and rinse aid dispenser.

Wide range of accessories and options available **on demand**: drying tunnel, steam condenser with or without heat recovery, steam exhauster, rinse aid dispenser and detergent dispenser.

Entry and exit tables available on demand.

Standard equipped with three racks for dishes, a rack for tableware and a rack for glasses.

IPX5 protection.

Option on demand: connection to cold water for a total power of 37,3 kW.







TECHNICAL SPECIFICATIONS

Width: 2170 mm Depth: 800 mm Height: 1580 mm Volume: 2.74 m³ Rack dimensions: 500x500 mm Useful height: 410 Electrical power: 28.30 kW Electric power: 230 V/ 3 - 400 V / 3+N/ 50-60 Hz Racks/Hour: 110-160-210 Dishes/Hour: 1980-2880-3780



