

# ATR5400ES

RACK CONVEYOR DISHWASHER LEFT-HAND SIDE ENTRY 5400 PLATES PER HOUR



## PRODUCT DESCRIPTION

**ATR5400 ES:** Rack conveyor dishwasher with **electric feeding** and **left-hand side rack entry**

Stainless steel structure 18/10 AISI 304. Sturdy counter-balanced door. Wash tank with rounded edges and inclination, thus ensuring the complete drainage of dirty water.

Stainless steel upper and lower wash and rinse arms that can be easily taken out for cleaning.

**One pre-washing area, a double washing area and a double rinsing area.**

**Three-speed rack movement** with a washing capacity of 190 racks/hour (speed 1) or 245 racks/hour (speed 2) or 300 racks/hour (speed 3).

High capacity **double-boiler system**.

**Double stainless steel surface filters** in the tank with an easily removable basket for collecting solid waste.

Compact geared motor with integrated clutch.

Ergonomic control panel in order to make the temperatures and the different working steps easily recognisable.

Possibility to program the water temperature in each wash tank and to set the rinsing temperature.

Standard equipped with non-return valve avoiding dirty water flowing back into the main water system (DVGW approved).

**Standard equipped** with stainless steel connection for detergent dispenser in each wash tank. **Standard equipped** with built-in connection for detergent dispenser and rinse aid dispenser.

Wide range of accessories and options available **on demand**: drying tunnel, steam condenser with or without heat recovery, steam exhauster, rinse aid dispenser and detergent dispenser.

Entry and exit tables available **on demand**.

**Standard equipped** with four racks for dishes, a rack for tableware and two racks for glasses.

**IPX5** protection.

**Option on demand:** connection to cold water for a total power of **49,7 kW**.



## TECHNICAL SPECIFICATIONS

**Width:** 3370 mm

**Depth:** 800 mm

**Height:** 1580 mm

**Volume:** 4.26 m<sup>3</sup>

**Rack dimensions:** 500x500 mm

**Useful height:** 410

**Electrical power:** 40.70 kW

**Electric power:** 230 V / 3 - 400 V / 3+N/ 50-60 Hz

**Racks/Hour:** 190-245-300

**Dishes/Hour:** 3420-4410-5400

